## EasiFit® T5 Ballast-Compatible Plastic LED Tube



# Specifications

**Socket Type** G5 (standard T5 lamp socket)

Efficacy 104-117 LPW

**Color** 30K, 35K, 40K, 50K

**CRI** > 80

**Input Voltage** 110V-277V (50-60Hz)

Operating Temp. -4°F-113°F

Power 28W

**Light Output** 2900lm to 3200lm

Beam Angle 185°

Warranty 5-years/50,000 hours

# **Ordering Information**

| Product # L     | Lumen                        | Color                            |
|-----------------|------------------------------|----------------------------------|
| LLT-4-T5-22-40K | 2900<br>3000<br>3200<br>3200 | 3000K<br>3500K<br>4000K<br>5000K |

### **Features**

- Direct-fit, plug & play with T5HO ballast
- Full nano plastic housing body, giving it the exact look and feel of fluorescent T5 and a very wide lighting angle
- Fits nicely into the existing T5 fixture without any rewiring
- Lighting is brighter

#### **Product Compliance & Certifications:**

- UL Type A certified
- DLC 4.2 qualified

## Description

Aleddra's EasiFit® T5 LED tube lamp is a UL Type A internal driver tube that is compatible with F54 T5HO ballasts. With a price almost comparable to a T5 tube, our EasiFit® tube lasts longer and has great energy savings. The end user can achieve savings on the retrofit investment.

The EasiFit® T5 LED tube features a full nano plastic body housing, giving it the exact look and feel of the fluorescent T5 and has a very wide lighting angle. The light is brighter and it fits nicely into the existing T5 fixture without any rewiring.