



DWR Downlight Wafer Remote

FEATURES

- Easily installs into drywall or suspended ceilings
- Includes remote driver/junction box
- FieldCCeT feature allows for multiple “set and forget” CCT options in each fixture

CERTIFICATIONS

- ETL Listed
- RoHS Compliant
- Wet Location Rated
- ENERGY STAR® Approved for superior energy efficiency
- 90 CRI models: Supports compliance with Title 24 (JA8)

PERFORMANCE

- Rated lifetime: L70: >50,000 hours
- 800 lm @ 13W
- 1,200 lm @16W
- 1,600 lm @ 20W
- 3000K CCT
- FieldCCeT: 27/30/35/40/5000K CCT
- CRI: >80; >90

ELECTRICAL

- Input voltage: 120V
- Triac dimming to 10%
- Power Factor: >0.9
- THD: <20%

THERMAL

- -4°F to 104°F (-20°C to 40°C) operating temperature

CONSTRUCTION

- Powder coated, die-cast aluminum housing
- Frosted lens for diffuse lighting
- IC Rated

WARRANTY

- 5-Year limited warranty available [online](#). Contact your EiKO sales rep for additional details.

project name	type
catalog number	voltage
approved by	date



APPLICATIONS

- Healthcare
- Hospitality
- Office
- Property Management
- Residential
- Retail

AVAILABLE MODELS

ORDER	ORDER CODE	ITEM #	SIZE	WATTS	CCT	LUMENS	EFFICACY (lm/W)	CRI	VOLTAGE	DIMMING	ENERGY STAR
	12132	DWR4/13W/830/120DT	4"	13W	3000K	800 lm	62 lm/W	80	120V	Triac	★
	12135	DWR4/13W/9CCT5/120DT	4"	13W	27/30/35/40/5000K	800 lm	90 lm/W	90	120V	Triac	★
	12133	DWR6/16W/830/120DT	6"	16W	3000K	1200 lm	75 lm/W	80	120V	Triac	★
	12136	DWR6/16W/9CCT5/120DT	6"	16W	27/30/35/40/5000K	1200 lm	90 lm/W	90	120V	Triac	★
	12134	DWR8/20W/830/120DT	8"	20W	3000K	1600 lm	80 lm/W	80	120V	Triac	★
	12137	DWR8/20W/9CCT5/120DT	8"	20W	27/30/35/40/5000K	1600 lm	90 lm/W	90	120V	Triac	★

MODEL CONFIGURATOR							
MODEL	SIZE	-	WATTS	-	CCT	-	VOLTAGE
DWR		-		-		-	

EXAMPLE PART NUMBER: DWR8/20W/830/120DT

ACCESSORIES

ORDER	ORDER CODE	ITEM #	DESCRIPTION
	11675	EEBE18WHA170S*	EIKO Emergency Battery External 18W 120-347V 170VDC

* **NOTE:** Only available on DWR4/13W and DWR6/16W. Field install only.

PRODUCT DIMENSIONS

