

CEILING FLUSH MOUNT
ML2 SERIES - BULB IN BOX



PRODUCT DESCRIPTION:

LED Flush Mount Ceiling Fixtures provide exceptional performance in general lighting applications for homes, hotels, motels, and commercial properties. The series is available in nickel, white, or bronze finishes with high transmission glass lens to complement virtually any décor. This bulb in a box solution comes prepackaged with JA8 compliant LED bulbs for ease of installation and guarantee of high CRI, flicker free LED performance.

FEATURES:

- CRI: ≥90
- JA8 compliant flicker free bulb included (E26)
- Dedicated Voltage: 120V, 60Hz
- Five year limited warranty
- Triac dimming standard
- Operating Temperature: 0°F to 104°F

CONSTRUCTION:

- Formed steel
- Powder coat finish
- High transmission lens

ORDERING*:

ORDER CODE	MODEL NUMBER	ITEM DESCRIPTION
1408622	ML2E242TRNI27	CEILING FIXTURE TRADITIONAL NICKEL FINISH WITH 2X12W 2700K JA8 COMPLIANT ENCLOSED RATED E26 SOCKET LED LAMP
1408623	ML2E242TRWH27	CEILING FIXTURE TRADITIONAL WHITE FINISH WITH 2X12W 2700K JA8 COMPLIANT ENCLOSED RATED E26 SOCKET LED LAMP
1408624	ML2E242TRBZ27	CEILING FIXTURE TRADITIONAL DARK BRONZE FINISH WITH 2X12W 2700K JA8 COMPLIANT ENCLOSED RATED E26 SOCKET LED LAMP

SPECIFICATIONS:

		ML2E242TRNI27	ML2E242TRWH27	ML2E242TRBZ27
ITEM	SPECIFICATION			
GENERAL PERFORMANCE	Power Consumption (W)	24 (2 x 12)	24 (2 x 12)	24 (2 x 12)
	Source Lumens	2,200	2,200	2,200
	Efficacy (lm/W)	92	92	92
	Color Temperature (K)	2700K		
	CRI	≥90		
	L70 Lumen Maintenance	25,000 hours		
ELECTRICAL	Input Voltage	120V		
	Input Frequency	60Hz		
	Power Factor	≥0.9		
PHYSICAL	Dimensions (L x W x H)	12.75" x 5.5" x 5.5"		
	Finish	Brushed Nickel, White, or Bronze		
	Operating Temperature	0°F to 104°F		
CERTIFICATION	Environment	Suitable for Damp Locations		
	Certification	Energy Star, ETL, FCC		
	Warranty	5 year limited warranty		