

## ML9LA17LCNBNI927



## ML9LA23LCNBNI927



### PRODUCT DESCRIPTION:

Wall Sconce, Contemporary brushed nickel glass >90 CRI 2700K

### FEATURES:

- 90 CRI
- 17W replaces a 60W incandescent
- 23W replaces a 100W incandescent

### CONSTRUCTIONS:

- Steel

DIMMER LIST	MANUFACTURE	DIMMER TYPE
MACL-153M	LUTRON	TRIAC (LE) INCAN
S-600P	LUTRON	TRIAC (LE) INCAN
SELV-300P	LUTRON	ELV (TE)
SCL-153P	LUTRON	TRIAC (LE) INCAN
CTCL-153P	LUTRON	TRIAC (LE) INCAN
6633-P	LEVITON	TRIAC (LE) INCAN
TGCL-153P-WH	LUTRON	TRIAC (LE) INCAN
AWSMG-MA	LEVITON	MLV (LE) INCAN
NTFTU-5A-277	LUTRON	TRIAC (LE) INCAN
AWSMG-EA	LEVITON	ELV (TE)

### ORDERING\*:

ORDER CODE	MODEL	WATTAGE	LUMENS	CCT
77655	ML9LA17LCNBNI927	17W	1500	2700K
77656	ML9LA23LCNBNI927	23W	2075	

\*Please contact your MaxLite representative to order products that don't have order codes listed here.

### SPECIFICATIONS:

#### ML9LA17LCNBNI927

#### ML9LA23LCNBNI927

ITEM	SPECIFICATION	DETAILS	
GENERAL PERFORMANCE	Spacing Criteria	Contact MaxLite for Installation Criteria	
	Color Temperature (CCT)	2700K	
	Delivered Lumens	1550 Lm	2075 Lm/w
	Efficacy (lm/W)	88 lm/W	85 Lm/w
	Dimming	Dimmable	
	Lumen Maintenance (L70)	>50,000 Hrs	
ELECTRICAL	Input Voltage	120-277V, 50-60 Hz	
	Driver Input Current (mA)	.142/ .061 mA max.	.192/ .083 mA max
	Power Consumption	17W	23W
PHYSICAL	Dimensions (L x W x H)	13.375"L x 7.875"W x 3" D	16.5"L x 9.8"H x 3.5"D
	Weight	2.8 lbs	4 lbs
	Housing	Metal	
	Lens	Art Glass	
	Mounting	Mount directly to J-Box	
	Operating Temperature	-4°F-113°F (-20°C-45°C)	
CERTIFICATION	Certification	FCC , UL, ES	
	Environment	Suitable for damp, install using only Class 2 power supply	
	LED Class	LM-80, ISTMT21	
	Warranty	5 years Limited Warranty	