## **B11**

## DECORATIVE B11 LED WITH STUNNING "LOTUS FLOWER" OPTIC



Add a beautiful, decorative look to almost any environment. This efficient B11 LED lamp adds simple, attractive lighting to your décor. With both clear glass and multiple output levels, it is a perfect lamp for your residential and decorative applications with a traditional appeal yet an energy-efficient, modern technology.

- **Decorative Lotus Optic:** Stunning lens provides glowing traditional warmth to any room
- Classic Styling: Add a room-enhancing touch to any application, including ceiling fans, chandeliers or almost anywhere seeking a special aesthetic
- Dimmable: Increase comfort, save energy and create a beautiful environment









## PRODUCT SPECIFICATIONS

SPECIFICATIONS <sup>1</sup>								
Color Temperature	2,700							
Output (Lumens)	244		350		550			
Power Factor	0.72		0.88		0.89			
CRI	81							
R9	6		6		5			
Efficacy (LN/W)	82		90		92			
Equivalent Source Standard	25		40		60			
Power Consumption (W)	3		4		6			
Base	E12	E26	E12	E26	E12	E26		
Dimmable	Yes							
Beam Angle	Omnidirectional							
Input Voltage (V)	120							
Operating Temperature Range (°F/°C)	-1 to +105 -18 to +40							
Product Dimensions (LxWxH in/cm)	1.47 x 1.47 x 4.53 3.7 x 3.7 x 11.5							
Weight (lbs/kg)	0.10 / 0.045							
Lumen Maintenance	15000							
Environmental Rating	Dry							
Certifications	UL, ES, FCC, RoHS							
Warranty	3 Years							

<sup>1</sup> Specifications and values supplied are nominal and are subject to change without notification; 2 Color temperatures conform to nominal CCTs as defined in ANSI Chromaticity Standard C78.377A; 3 Lumen measurement complies with IES LM-79-08 testing procedures; 4 Please consult with Lighting Science Group for a list of compatible dimmers; 5 Lumen maintenance calculations are based on measurements that comply with IES LM-80-08 testing procedures. L70 = 70% lumen maintenance, or when lamp reaches 70% of initial output

## ORDERING INFORMATION

FAMILY	PRODUCT	WATTAGE EQUIVALENT	COLOR TEMPERATURE	BASE	VOLTAGE	PACKAGING
LSPRO	B11	25WE	W27 - Soft White (2700K)	E12	120	3PK - Three Pack Box
		40WE		E26		
		60WE				

example: LSPro B11 60WE W27 E12 120 3PK



LSPro\_B11\_SpecSheet\_RevA