

PROJECT NAME:_

CATALOG NUMBER:_

NOTES:__

FIXTURE SCHEDULE:

Page: 1 of 1

Torchiere

ORDFRING:

ML1E SERIES - BULB IN BOX



2700K

PRODUCT DESCRIPTION:

LED Torchieres provide long-lasting illumination and energy cost savings for general and accent lighting applications. Offered in black, nickel, or white finish, the Torchiere has a half shade that provides even illumination and a die cast steel body ensures enduring style and durability. This bulb in a box solution comes prepackaged with JA8 compliant LED bulbs for ease of installation and guarantee of high CRI, flicker free LED performance.

FEATURES:

- · Half shade diffuser
- Dimming capability
- Even distribution of light
- CRI: ≥90
- Flicker free bulb included (E26 Base) [Supports Compliance of JA8-2016-E & CEC T20]
- Dedicated voltage 120V, 60Hz
- Five-year limited warranty
- Operating Temperature 0°F to 104°F

CONSTRUCTION: WARRANTY:

- Steel construction
- Powder coat finish
- Glass half shade •

5-year standard warranty* (further details available at www.maxlite.com/warranties) *Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

	ORDER CODE	MODEL NUMBER	ITEM DESCRIPTION		
	1410154	ML1E242DARBK27-V2	TORCHIERE ARCHITECTURAL BLACK FINISH WITH 2 X 12W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP		
	1410155	ML1E242DARWH27-V2	TORCHIERE ARCHITECTURAL WHITE FINISH WITH 2 X 12W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP		
	1410156	ML1E242DARNI27-V2	TORCHIERE ARCHITECTURAL NICKEL FINISH WITH 2 X 12W 2700K JA8 COMPLIANT E26 SOCKET LED LAMP		

SPECIFICATIO	NS:	ML1E242DARBK27-V2	ML1E242DARWH27-V2	ML1E242DARNI27-V2	
ITEM	SPECIFICATION	DETAILS			
	Power Consumption (W)	24 (2 × 12W)	24 (2 x 12W)	24 (2 × 12W)	
	Source Lumens	2,200 lm	2,200 lm	2,200 lm	
GENERAL	Efficacy (Im/W)	91.7 lm/W	91.7 lm/W	91.7 lm/W	
PERFORMANCE	Color Temperature (K)	2700K			
	CRI	≥90			
	L70 Lumen Maintenance	25,000 hours			
	Input Voltage	120V			
ELECTRICAL	Input Frequency	60Hz			
	Power Factor	≥0.9			
	Dimensions (L x W x H)	10" x 10" x 70"			
PHYSICAL	Finish	Black, White, Brushed Nickel			
	Operating Temperature	0°F to 104°F			
	Environment	Suitable for Damp Locations			
CERTIFICATION	Certification		Energy Star, ETL		
	Warranty		5-year standard warranty*		