

PROJECT NAME:\_\_\_\_\_CATALOG NUMBER:\_

NOTES:\_

FIXTURE SCHEDULE:

Page: 1 of 1

# **CEILING FLUSH MOUNT** BULB IN BOX









#### **PRODUCT DESCRIPTION:**

LED Flush Mount Ceiling Fixtures provide exceptional performance in general lighting applications for residential, multi-unit residential, hotels, and commercial properties. The series is available in nickel, white or bronze finishes with a high-transmission glass lens to complement virtually any décor. This bulb in a box solution comes prepackaged with JA8 compliant LED bulbs for ease of installation and guarantee of high CRI, flicker free LED performance.

### **FEATURES:**

- Ficker free bulb E12A19D927/JA8 included [Supports Compliance of JA8-2016-E]
- ETL listed for damp locations
- Voltage / Frequency: 120V, Triac Dimming, 60 Hz
- CRI: ≥90 available
- Operating temperature: -4°F to 104°F (-20°C to 40°C)
- Rated Life: L70 ≥ 50,000 Hours
- Construction: Die formed steel
- Warranty: 5 Years
- · Powder coat finish
- High Transmission lens

## WARRANTY:

5-year standard warranty\* (further details available at www.maxlite.com/warranties)

\*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

### **ORDERING\*:**

FAMILY		ТҮРЕ	OUTPUT		STYLE		FINISH		CCT/CRI		CAPABILITIES		
ML2=	Ceiling Flush Mounts	E=	Edison Base E26 Bulb included	242=	2 x 11W Lamps, 120V	TR=	Traditional	NI= WH=	Nickel White	27=	2700K, 90 CRI	-V2=	JA8 Compliant Bulb

SPECIFICATIO	NS:	1408622 ML2E242TRNI27-V2	1408623 ML2E242TRWH27-V2					
ITEM	SPECIFICATION							
	Power Consumption (W)	22						
	Source Lumens	2,200	2,200					
GENERAL	Efficacy (Im/W)	92	92					
PERFORMANCE	Color Temperature (K)	2700K						
	CRI	≥90						
	L70 Lumen Maintenance	25,000 hours						
	Input Voltage	120V						
ELECTRICAL	Input Frequency	60Hz						
	Power Factor	≥0.9						
	Dimensions (D x H)	12.75" x 5.5"						
PHYSICAL	Material	Die formed steel metal, Frosted glass lens						
	Operating Temperature	0°F to 104°F						
	Environment	Suitable for Damp Locations						
CERTIFICATION	Certification	Enery Star, ETL						
	Warranty	5-year standard warranty*						

