


JOB NAME: _____


DATE: _____

TYPE: _____



DIMENSIONS:

1/4" (Thick)



RSL10-MCT5

LED CCT5 ULTRA SLIM RECESSED LIGHT

Ideal for New as well as old residential and commercial constructions.

ELECTRICAL SPECIFICATIONS:

- Voltage: 120VAC
- Wattage: 20W
- Power factor: >0.90
- Efficacy: 75LM/W

HOUSING SPECIFICATIONS:

- 1/4" Thick
- Die-cast Aluminum with white powder coat finish
- Pot light housing is not required even for insulated ceiling
- Junction box 1" thick included with fixture
- Type IC rated: Approved for direct contact with insulation
- Operating temperature: -40°F ~ 104°F
- Lifespan: 50,000 Hrs.
- Air-tight and damp location approved

CERTIFICATIONS: ETL



OPTIONAL ACCESSORIES:



RSL-EXT-10FT-MCT

MODEL	DESCRIPTION
RSL-EXT-10FT-MCT	10 Ft. Extension Cable For use with all MCT Slim Light

LIGHTING SPECIFICATIONS:

- Dimming: dimmable
- Lens: 0.125" white translucent acrylic
- Optics: White translucent acrylic
- LED: Seoul DOB (Driver On Board) Technology
- Total lumens: 1500LM
- Color temperature:
MCT: 2700K/3000K/3500K/4000K/5000K
- Color rendering index: >80
- Beam Angle: 100° - 110°

WARRANTY: 5 years



JOB NAME: _____

DATE: _____

RSL10-MCT5

LED CCT5 ULTRA SLIM RECESSED LIGHTS

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
RSL10-MCT5	20W	120VAC	1500LM	MCT

BRAND OF DIMMERS:

NO.	BRAND	MODEL
1	Leviton	6631-1LT
2	Lutron	MACL-153MLH-AL
3	Lutron	TGCL-153PH-LA
4	Lutron	DVW-603PGH-WH
5	Lutron	CT-600PR-WH
6	Lutron	LGCL-153PHL-IV
7	Pass & Seymour	HCL453PTCCCV6
8	Pass & Seymour	LSLV603PWV

