

LEDone

Projects:

Comments:

4ft T8 12W Shatterproof Glass Tube Spec

SPECIFICATIONS:

WATTAGE:	12W LOD-GDMT84F-12W40KC LOD-GDMT84F-12W50KC LOD-GDMT84F-12W40KF LOD-GDMT84F-12W50KF
MODEL #:	
LISTED:	ETL/CETL/FCC
VOLTAGE:	100VAC-277VAC
POWER FACTOR:	0.9
FREQUENCY:	50-60Hz
LUMENS:	1,900/1,800LM
LUMENS EFFICIENCY:	158/150LM/W
KELVIN (CCT):	4000K / 5000K
THD:	20%
CRI:	80
IP RATING:	IP20
BEAM ANGLE & BASE:	270 degree / G13
LENS:	Frosted
MATERIALS:	Glass + PC
POWER:	Internal Isolation
LED CHIPS:	San An
LIFE SPAN (HOURS):	50,000hrs
DIMMING COMPATIBLE:	No
LENGTH OF WARRANTY:	5 years
PRODUCT LENGTH:	4ft(1200mm)
PRODUCT DIAMETER:	1in(26mm)
WEIGHT:	180G
WORKING ENVIRONMENT:	-20°C to 40°C (-4°F to 104°F)
SUGGESTED REPLACEMENT FOR:	Fluorescent Tube 36W
PERCENTAGE OF WATTAGE SAVED:	>60%

3000K: Special order

Features:

Provides exceptional lighting, energy efficient, and low in maintenance cost. Shatterproof glass Type A & B.

Applications:

T8 Linear Tube retrofits are used in commercial buildings such as hotels, conference rooms, schools, and office buildings.

